

Geoflex



Liquid Plastic Waterproofing

Description:

Geoflex is a flexible, acrylic-based Waterproofing Liquid.

It is a waterproof coating that affords excellent protection against the ingress of rainwater and dampness, has a high resistance to ultra-violet

Application:

Apply one coat Geoflex Primer, by means of brush or roller, to prepared surface at the rate of 6-7 square metres per litre. Allow to dry.

SYSTEM A

Polypropylene reinforced (Smooth surfaces). Apply a base coat of Geoflex to the primed surface, by means of brush or roller, at the rate of approximately half a litre per square metre and immediately embed a layer of 30gm polypropylene fabric, smoothing with a brush. Allow to dry. Apply a second coat of Geoflex Liquid Plastic at the rate of approximately 1 litre per square metre. Allow to dry. Apply a third coating, if necessary, so as to ensure total cover of the fabric.

SYSTEM B

Un-reinforced. (Face brick surfaces) Apply Geoflex in two or three coats, by means of brush, at the total coverage rate of approximately 1 litre per square metre to the pre-primed surface. Allow for drying between coats.

Application should be undertaken at ambient

Applications:

- Walls
- Parapets
- Small areas

Nominal coverage:

1.2 m² per litre



Surface preparation:

Surface preparation, as with all waterproofing installations, is of paramount importance to the success and long-life of the system. Ensure that the surface to be treated is dry and sound, free of loose, dusting or flaking particles and free from contaminants such as grease and fungus.

Precautions:

Do not apply when rain is imminent.

Brushes and utensils may be cleaned with water immediately after use.

Geoflex is a Waterproof coating and not a decorative paint - but may be overcoated with a high quality